



30Watt/26° - 301.66.26.R044.230
30Watt/38° - 301.66.38.R044.230
30Watt/44° - 301.66.44.R044.230

40Watt/26° - 301.66.26.R044.240
40Watt/38° - 301.66.38.R044.240
40Watt/44° - 301.66.44.R044.240

60Watt/26° - 301.66.26.R044.260
60Watt/38° - 301.66.38.R044.260
60Watt/44° - 301.66.44.R044.260

High quality, die cast aluminium recessed COB downlights that can be installed into all types of applications. With a high power LED and funnel coated in patented reflective technology, this recessed downlight gives a strong, well distributed beam of light which is perfect for general lighting applications where good illumination is essential.

30W/40W/60W     silver  black  white    Dimmable

Specification

Operational Voltage	AC85V~265V	AC85V~265V	AC85V~265V
Power Consumption	30W	40W	60W
Beam Angle	26° /38° /44°	26° /38° /44°	26° /38° /44°
Color Temperature	2700K~5000K	2700K~5000K	2700K~5000K
CRI	Ra=80~90	Ra=80~90	Ra=80~90
Intensity of Light Output	1620lm~2000lm	2200lm~2800lm	3200lm~3800lm
Driver	include	include	include
Expected Life	50,000hours	50,000hours	50,000hours
Rating	IP64	IP64	IP64


cut out hole: 310mm*160mm

